


Video distributor



Specification	Order No.	Packing unit	PS	EAN
	1226 00	1	10	4010337229919

Features

- The video distributor is an active component for line adjustment of the video signal.
- The video distributor distributes the video signal of the door stations, DCS-camera gateways and DCS-IP gateways to the home stations.
- The video distributor is required when the cable routing to the video components of the Gira door communication system is implemented as a branch line.
- The video distributor ensures the proper terminating resistance to prevent possible reflections of the individual branches and the resulting picture disturbances.

The combination housing makes three mounting types possible

- Surface-mounted (in a standard junction box).
- Flush-mounted (in a device box).
- As a DRA device (using the DRA adapter enclosed).

Technical data

Power supply:	DC 26 V ± 2 V (by 2-wire bus)
Connections	
- 2-wire bus IN:	2 x screw terminal
- 2-wire bus OUT:	6 x screw terminal
Ambient temperature:	-25 °C to +70 °C

Notes

- The video distributor is cascable. A total of up to 15 video distributors and video multiplexers can be used in one system.
- No further configuration is necessary during commissioning because the video distributor automatically adapts to the existing mains supply.

Scope of supply

- A DRA adapter is included.

Dimensions in mm

Video distributor:	B 36	H 52	T 27
--------------------	------	------	------
