


## Wind Sensor - Standard



Specification	Order No.	Packing unit	PS	EAN
	0913 00	1	06	4010337913009

## Features

Wind transmitter (cup anemometer/anemometer)

- The wind sensor enables raising of the blinds depending on the strength of the wind, for example. In this way, sensitive blind slats can be protected from increasing wind.
- The wind transmitter is used to convert the wind speed into electrical signals.
- It is mounted on the roof or on the side of the building and connected to the evaluation unit.

Evaluation unit

- Test mode with test LED.
- Distributor terminals for connecting a heated wind signaller.

## Technical data

Wind transmitter

- Material of the transmitter and cup anemometer: Plastic (ABS), black
- Ambient temperature: -25 °C to +60 °C
- Connection cable: LIYY 2 x 0.14 mm<sup>2</sup>, length 3 m (can be extended to max. 50 m)

Evaluation unit

- Wind warning range: 3.3 to 24.5 m/s, can be set to one of 8 levels
- Switching contact: Relay with zero-voltage NO contact
- Load capacity: max. 2 A
- Operating voltage: AC 230 V

## Scope of supply

- Mounting bracket included in the scope of supply.

# GIRA Data sheet

catalogue.gira.com

© Copyright by  
Gira Giersiepen GmbH & Co. KG  
All rights reserved

www.gira.com

## Dimensions in mm

Cup diameter of the wind transmitter:      Ø 134      H 160

---