


Wind sensor Standard



Specification	Order No.	Packing unit	PS	EAN
	0913 00	1	06	4010337913009

Features

- The wind sensor enables e.g. blinds to be raised depending on the wind strength. In this way, sensitive blind slats can be protected from increasing wind.
- Recording and evaluating wind speeds.
- 8 adjustable wind strengths.
- Wind alarm is triggered 15 seconds after the set wind strength threshold is exceeded.
- Test run for function testing.
- Evaluation unit: Surface-mounted device for indoor installation in dry rooms.
- Wind transmitter: Device for outdoor installation.

Technical data

Wind transmitter

- Material of the transmitter and cup anemometer:
- Ambient temperature:
- Connection cable:
- Protection class:

Plastic (ABS), black

-20 °C to +55 °C

JY-ST-Y 2 x 0.6 mm², length 3 m (can be extended to max. 50 m)

IP55

Evaluation unit

- Wind warning range:
- Switching contact:
- Load capacity:
- Operating voltage:
- Protection class:

3.3 to 24.5 m/s, can be set to one of 8 levels

Relay with zero-voltage NO contact

max. 2 A

AC 230?V

IP20

Dimensions

- W x H x D:

110 mm x 99 mm x 38 mm

Scope of supply

- Mounting bracket included in the scope of supply.

Dimensions in mm

Cup diameter of the wind transmitter:	Ø 134	H 160
---------------------------------------	-------	-------
