© Copyright by Gira Giersiepen GmbH & Co. KG

All rights reserved

www.gira.com

Profile 55 with angled mounting bracket 8-gang

GIRA Data sheet



| Specification | | Order No. | Packing unit | PS | EAN |
|---------------|---|-----------|--------------|----|---------------|
| | aluminium pure white glossy (lacquered) | 1198 27 | 1 | 17 | 4010337198277 |
| | aluminium | 1198 26 | 1 | 17 | 4010337198260 |

Features

- Installation profile of aluminium for horizontal and vertical installation.
- With cable and duct inlet. The cable entry can be flush-mounted or surface-mounted.
- Simplified installation due to clippable inserts.

Notes

- With System 55, rocker switches, buttons, and SCHUKO socket outlets with hinged covers are generally drip-proof (IP21) on the wall in conjunction with these housings.
- Key switches and three-stage switches cannot be installed in this housing.
- Using the angled mounting bracket or base feet, the Profile 55 can be installed as a table-top housing, as well as under hanging cabinets or in corners.

| Dimensions in mm | | | |
|------------------|-----|-----|-----|
| 2-gang: | 158 | 107 | 107 |
| 3-gang: | 230 | 107 | 107 |
| 5-gang 600mm: | 587 | 107 | 107 |
| 8-gang: | 587 | 107 | 107 |