


KNX pushbutton sensor 3 Komfort, 3-gang



Specification	Order No.	Packing unit	PS	EAN
 pure white glossy	2033 112	1/5	06	4010337081821

Features

- Mounting on bus coupler 3.
- Disassembly safeguard by screw connection.
- Two multicoloured status LEDs per operating surface.
- Integrated temperature sensor for measuring and forwarding the ambient room temperature.
- Rocker or button function can be set for each operating surface.
- Rocker function: switching, dimming, blind control, value transmitter 1 byte, value transmitter 2 bytes, and scene auxiliary unit.
- Button function: Switching, dimming, blind control, value transmitter 1-byte, value transmitter 2-byte, scene auxiliary unit, and room temperature controller auxiliary unit.
- Controller auxiliary unit: Operating mode changeover with normal and high priority, defined selection of operating mode, toggle between various operating modes, switching of presence condition, setpoint offset.
- Blocker for blocking individual button or rocker functions.
- Alarm message displayed through all LEDs flashing.
- Multicoloured status LED (red, green, blue) can be configured globally or separately. A superimposed function can be activated on the bus whereby the colour and display information of individual status LEDs can be modified according to priority.
- White operating LED.
- Operating LED ON, OFF, automatic switch-off, or switchable via object.
- Communication object for brightness control of status LED and operating LED (e.g. for reducing brightness in bedrooms at night).

Technical data

Ambient temperature:	-5 °C to +45 °C
Protection class:	III

Notes

- Professional labelling with the Gira Inscription Service www.marking.gira.com.

Scope of supply

- Blank inscription labels included.
