


Gira System 3000 DALI power control unit, flush-mounted insert



Specification	Order No.	Packing unit	PS	EAN
	5406 00	1	02	4010337048275

Features

- For switching on/off and adjusting brightness for lights with a DALI interface
- Adjustment of colour temperature for lights with DALI Device Type 8 for Tunable White according to IEC 62386-209.
- Connecting auxiliary units is possible.
- DALI power supply for 18 DALI devices.
- Parallel connection of up to 4 DALI Power control units to supply up to 72 DALI devices.
- Save the minimum brightness, the coolest and warmest colour temperature.
- Switch on with the last brightness/colour temperature set, or a saved brightness/colour temperature.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Power consumption:	max. 2.8 W
DALI rated voltage:	DC 16 V (typ.)
Output current:	max. 36 mA
Number of DALI devices:	max. 18
Number of DALI Power control units that can be connected in parallel:	max. 4
Colour temperature adjustment:	2000 to 10000 K
Auxiliary inputs	
- Non-illuminated mechanical buttons:	unlimited
- Auxiliary insert, 2-wire:	unlimited
- Auxiliary insert, 3-wire:	max. 10
Installation depth:	30 mm
Installation:	in device box pursuant to DIN 49073
Ambient temperature:	-5 °C to +45 °C

GIRA Data sheet

catalogue.gira.com

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com
