


eNet wireless switching or momentary-contact actuator, 8-gang / blind actuator, 4-gang



Specification	Order No.	Packing unit	PS	EAN
 DRA	5435 00	1	42	4010337774280

Features

- The eNet wireless switching, wireless momentary-contact, or blind actuator receives telegrams for switching lighting or controlling electrically-operated hangings from the eNet wireless reception module or eNet server via a data cable.
- Two outputs are each operated in the same mode (switching, dimming, blind or shutter).
- Switching of lighting or single-phase fan motors.
- Control of electrically operated hangings, such as blinds, shutters, or awnings
- Operating modes: switching actuator, momentary-contact actuator can be set for a single output; a blind actuator, shutter actuator can be set for a pair of outputs.
- Status feedback to eNet wireless transmitter.
- Scene operation.
- Operating mode buttons: Relay contact stays closed as long as telegrams are being received (max. 60 seconds).
- Positioning of blind and slat using scene call-up.
- Positions for sun protection and twilight can be saved.
- Threshold value scenes for sun protection, twilight and wind alarms.
- Hanging period can be saved.
- Slat adjustment time can be saved.

Can be set with eNet server:

- Flashing function.
- Delay time.
- Switch-on/off delay.
- Switch-off pre-warning.
- Minimum switching repeat time.
- Permanent-on, permanent-off.
- Adjustment time when changing directions.
- Motion direction can be inverted (e.g. for roof windows).
- Position for sun protection, twilight, lock-out protection, and wind alarms.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Standby:	max. 0.5 W
Ambient temperature:	-5 °C to +45 °C

Switching capacity AC 230 V:	16 A / AC1
Connected load	
- Light bulbs:	2300 W
- HV halogen lamps:	2000 W
- Wound transformer:	1000 VA
- Tronic transformer:	1500 W
- Fluorescent lamps, uncompensated:	920 VA
- LED lamps:	typ. 500 W
- Compact fluorescent lamp:	typ. 500 W
- Motors:	1000 W
- Capacitive load:	690 VA (560 μ F)
Connections:	max. 4 mm ²
Length of the data cable:	Max. 3 m

Notes

- An eNet wireless reception module or an eNet server is required to operate this DIN-rail mounting device.
 - Wireless approval is valid for EU and EFTA countries.
-

Dimensions

Modular widths (MW):	4
----------------------	---
