


Wind sensor Standard



Specification	Order No.	Packing unit	PS	EAN
	0913 00	1	06	4010337913009

Features

- The wind sensor enables e.g. blinds to be raised depending on the wind strength. In this way, sensitive blind slats can be protected from increasing wind.
- The wind transmitter is used to convert the wind speed into electrical signals.
- It is installed on the roof or on the side of the building and connected to the evaluation unit.
- Test mode with test LED.
- Test run for function testing.
-

Technical data

Wind transmitter

- Material of the transmitter and cup anemometer: Plastic (ABS), black
- Ambient temperature: -20 °C to +55 °C
- Connection cable: JY-ST-Y 2 x 0.6 mm², length 3 m (can be extended to max. 50 m)
- Protection class: IP55

Evaluation unit

- Wind warning range: 3.3 to 24.5 m/s, can be set to one of 8 levels
- Switching contact: Relay with zero-voltage NO contact
- Load capacity: max. 2 A
- Operating voltage: AC 230?V
- Protection class: IP20

- W x H x D: 110 mm x 99 mm x 38 mm

Scope of supply

- Mounting bracket included in the scope of supply.

GIRA Data sheet

catalogue.gira.com

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com

Dimensions in mm

Cup diameter of the wind transmitter: Ø 134 H 160
