# **GIRA** Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

## Antenna socket insert (SE33ST)



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
	0937 00	1/5	31.94	01	4010337937005

#### Features

- Stub cable outlet with three connections.

- The IEC plug for terrestrial TV is located on the bottom left, the IEC socket for FM (radio) on the bottom right and at the top centre is the F connector for satellite TV (SAT).
- Channel filter for terrestrial and satellite television with high attenuation rate: The SAT signal is filtered in the FM-TV-IEC connections, while the terrestrial FM/TV signal is filtered in the satellite F connection.
- DC feed-through from the SAT connection to the input.
- The internal conductor is connected simply by pressing it, without the need for screws. Internal conductor can thus be removed multiple times.
- Complies with shield class A.

## **Technical data**

UKW frequency band - Frequency range: - Decoupling:	87.5 to 108 MHz > 10 dB
UKW frequency band:	4 dB
TV frequency band - Frequency range: - Decoupling: - Attenuation: TV plug:	125 to 862 MHz > 10 dB 4 dB
SAT frequency band - Frequency range: - Decoupling: - Attenuation: SAT plug:	950 to 2400 MHz > 20 dB 1.5 dB
Installation depth:	36 mm

# **GIRA** Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Notes

- For screw attachment only.