


## DALI flush-mounted rotary dimming insert



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
	2026 00	1	63.90	02	4010337129592

### Features

- Brightness adjustment for lights with a DALI interface.
- Adjustment of colour temperature for lights with DALI Device Type 8 for Tunable White according to IEC 62386-209.
- Rotary auxiliary unit (input device) for higher-level DALI-2 controls.

#### Product characteristics without programming

- DALI-2 application controller without bus power supply requires an external DALI power supply in accordance with IEC 62386-101.
- Multimaster-compatible.
- LED for device localisation.
- Saving the base brightness and a switch-on brightness.
- Saving the colour temperature limit values.

#### Product characteristics through programming via DALI-2 control commands

- Suitable as rotary auxiliary unit (input device) for connecting to central DALI-2 controls.
- Supports four DALI-2 instances for adapting to central control.
- Can be used for controlling a DALI-2 group.
- Cyclical transmission of control commands to DALI operating devices can be activated. Device function depends on configuration

### Technical data

DALI rated voltage:	DC 16 V (typ.)
Current consumption:	max. 4 mA
Colour temperature adjustment:	2000 to 10000K
Ambient temperature:	-5 °C to +45 °C