catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

DALI potentiometer Tunable White with integrated power supply unit

GIRA Data sheet



| Specification | Order No. | Packing unit | £/piece without VAT | PS | EAN |
|---------------|-----------|--------------|------------------------|----|---------------|
| 0 | 2030 00 | 1 | 151.86 | 02 | 4010337023470 |

Features

- Switching and brightness adjustment for lights with a DALI interface.
- Adjustment of the colour temperature for lights with a DALI device type 8 (colour type: colour temperature) for Tunable White in accordance with IEC 62386-209
- Integrated power supply in accordance with the DALI specifications (DIN IEC 60926) for 26 DALI devices.
- Parallel connection of up to 4 DALI potentiometers with integrated power supply unit to supply up to 104 DALI devices.
- Can be operated simultaneously from several control points. Communication is via Broadcast.
- Colour temperature limits and a basic brightness or a switch-on brightness can be stored.

Technical data

Rated voltage: AC 230 V, 50/60 Hz

max. 2 W Power consumption:

DALI rated voltage: DC 16 V (typ.)

Output current: max. 52 mA

Number of DALI devices: max. 26

Number of DALI potentiometers with integrated power supply unit that can be

connected in parallel:

max. 4

2000 to 10000K Colour temperature adjustment:

Max. 4 mm² Single-wire connection:

Installation depth: 32 mm

-5 °C to +45 °C Ambient temperature:

GIRA Data sheet

catalogue.gira.com

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

- When selecting the DALI power supply, the number of DALI devices and the DALI potentiometer (always counts as 1 device) must be factored in.