GIRA Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

LED orientation light 230 V~ white



| Specification | Order No. | Packing unit | £/piece without VAT | PS | EAN |
|---------------|-----------|--------------|------------------------|----|---------------|
| white | 2361 00 | 1 | 88.51 | 02 | 4010337084907 |
| warm white | 2364 00 | 1 | 88.51 | 02 | 4010337121749 |

Features

- LED orientation light for use in the private and commercial sectors.

- The orientation light is used, for example, to illuminate stairs or as an orientation aid in dark rooms.

- The brightness of the light can be set individually.

- A film which can be inscribed individually can be laid in the cover plate.

- Pictograms for room and route marking can be inserted.

Technical data Rated voltage: AC 230 V, 50 Hz 1.7 W/8.5 VA Power consumption: 3 to 100 % Brightness range: Number of LEDs: 4 Colour temperature Approx. 5000 K - White: Installation depth: 30 mm Connection cross section - maximum: 1.5 mm² Ambient temperature: 0 °C to +40 °C

catalogue.gira.com

GIRA Data sheet

© Copyright by Gira Giersiepen GmbH & Co. KG All rights reserved

www.gira.com

Notes

- Professional inscription by the Gira inscription servicewww.marking.gira.com.