


## eNet wireless switching or momentary-contact actuator, 1-gang



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
 DRA	5433 00	1	108.90	42	4010337774273

### Features

- The eNet wireless switching or wireless momentary-contact actuator receives telegrams for switching lighting from the eNet wireless reception module or eNet server via a data cable.
- Operating modes: Switching actuator or momentary-contact actuator.
- Status feedback to eNet wireless transmitter.
- Scene operation.
- Operating mode buttons: Relay contact stays closed as long as telegrams are being received (max. 60 seconds).

Can be set with eNet server:

- Flashing function.
- Delay time.
- Switch-on/off delay.
- Switch-off pre-warning.
- Minimum switching repeat time.
- Permanent-on, permanent-off.

### Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Standby:	max. 0.2 W
Ambient temperature:	-5 °C to +45 °C
Switching capacity AC 230 V:	16 A / AC1
Connected load	
- Light bulbs:	2300 W
- HV halogen lamps:	2000 W
- Wound transformer:	1000 VA
- Tronic transformer:	1500 W
- Fluorescent lamps, uncompensated:	920 VA
- LED lamps:	typ. 500 W
- Compact fluorescent lamp:	typ. 500 W

- Capacitive load: 690 VA (560  $\mu$ F)

Connections: max. 4 mm<sup>2</sup>

Length of the data cable: Max. 3 m

---

## Notes

- An eNet wireless reception module or an eNet server is required to operate this DIN-rail mounting device.

---

## Dimensions

Modular widths (MW): 2

---