








## System 106 blank module



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
 stainless steel	5568 920	1	65.06	20	4010337022862
 aluminium	5568 926	1	48.18	20	4010337022855
 traffic white (laquered)	5568 902	1	38.55	20	4010337022848
 stainless steel V4A	5568 914	1	81.32	20	4010337092049
 bronze	5568 921	1	81.32	20	4010337100911
 black matt	5568 925	1	81.32	20	4010337100751

The Gira System 106 is an installation system made of metal in a puristic and elegant frameless design, based on basic measurements of 106.5 × 106.5 mm. With the modular door intercom in Gira System 106, hospitality begins even before you reach the front door. All the functions are presented in a harmonious overall appearance, from the call button module, intercom module, and camera module, up to the info and blank module. In the dark, backlit call buttons with inscription space ensure good legibility and an attractive appearance.

### Individually adaptable modular system

The System 106 can be used in family homes or apartment buildings, as well as in office buildings, industrial properties, and hotels. The modular design enables the system's size, design, and functionality to be individually adapted to the respective requirements. Expansions and changes are possible at any time by easily exchanging the modules.

With this system, it is also possible to exchange the fronts only. This means that the appearance of the system can be changed from e.g. traffic white to a stainless steel surface at a later stage, without having to exchange the electronic units.

### High-quality materials

The modules are frameless with design fronts made of genuine materials, available in two brushed stainless steel versions (V2A and V4A), anodised aluminium C-0, and a metal alloy lacquered in traffic white (RAL 9016): all robust materials which ensure durability. The camera and DIN 18040 display module feature a black glass cover.

#### Easy and phased installation

The system can be installed in phases, in parallel to the progress of building work. In this way, it is possible to initially install only the lower part of a surface-mounted housing during construction of the shell; cables and modules can then be added when they are needed.

#### Individual inscription options

Call button modules and info modules can be labelled individually via the Gira inscription service.

---

### Features

- Leaves a space for future applications and serves as a design element for realising large door stations in the system style.

---

### Technical data

#### Connections

- System: 2 x connector strip

Ambient temperature: -25 °C to +70 °C

Protection class: IP54

---

### Notes

- The info module must be selected for an inscribable variant.

---

### Dimensions in mm

B 106,5      H 106,5      T 28,7